

MAINTENANCE PLAN

WEEKLY MAINTENANCE	YES	NO	N/A
1. Remove waste that there might be on the dock or at the working area.			
2. Make sure that the hinge is completely clean.			
3. Check the material we have in Stock, for a correct maintenance.			

Comments:

MAINTENANCE EVERY 90 DAYS	YES	NO	N/A
1. Perform the daily maintenance.			
2. Lubricate the hinges and moving parts of the ramp (cylinder pins)			
3. Check the condition of the bridge structure, pins, bolts, etc.			
4. Check the oil level in the hydraulic unit (the correct level is indicated on the reservoir; recommended oil: UNIL-OPAL HFO 46)			
5. Check the condition of the control panel, hoses, junction boxes, sensors, etc. If condensation is observed inside the control panel or junction boxes, check the seals, connections and holes drilled for assembly, and make the necessary modifications to prevent condensation			
6. Check the condition of the external impact buffers.			
7. Check the condition of the bridge anchorage to the metallic profile.			
8. Check the condition of the dock leveller anchorage to the floor.			

Comments:

MAINTENANCE EVERY 180 DAYS	YES	NO	N/A
1. Perform the recommended maintenance every 90 days.			

Comments

MAINTENANCE EVERY 360 DAYS	YES	NO	N/A
1. Perform the recommended maintenance every 90 and 180 days.			

Comments: