



ALAPONT
GLOBAL

Industrial platforms

SINGLE-COLUMN PLATFORM

Alapont's single-column industrial lift platforms are designed to lift **loads from 150 kg to 3,000 kg**. They offer a wide range of dimensions, travel distances, and stopping points. Models with an inverted chassis are available, allowing the platform and its guides to be flush with the final floor level.

- **Custom-made travel** distances and platform sizes.
- Load capacity from **150 kg to 3,000 kg**.
- **Maximum travel distance of 12 m**.
- Non-slip surface.
- Cable slack or breakage detection system.
- Hydraulic safety parachute.
- **Nominal speed of 0.1 m/s (optional 0.2 m/s)** and end-of-travel safety timer.
- Surface-mounted external control buttons with mushroom-head emergency stop.
- Models with an inverted chassis are available, allowing both the platform and its guides to be flush with the final floor level.



REGULATIONS AND CERTIFICATION

98/371/CE



TECHNICAL FEATURES

LOAD (Kg)	(I) WIDTH (mm)		(G) BOTTOM (mm)		A (mm)			F (mm)	L (mm)	Flight	Reacc.
	Max.	Min.	Max.	Min.	PRH.1	PRH.1(2)	PRH.1.1			(Min)	(Kg)
150	1.200	550	900	500	100	/	750	120	430	1.340	1.000
300	1.500	750	1.300	600	210	/	750	155	610	1.500	1.400
400	1.500	750	1.300	600	210	/	750	155	610	1.500	1.600
500	2.000	940	1.300	600	210	450	900	155	805	1.560	1.800
750	2.500	950	1.500	800	210	550	1.000	180	805	1.560	2.200
1.000	2.700	1.150	2.000	800	250	550	1.00	205	1.000	1.800	2.800
1.500	3.000	1.150	2.000	800	270	650	1.250	230	1.000	1.980	3.400
2.000	3.500	1.650	2.000	1.000	280	650	1.500	230	1.000	2.000	4.200
3.000	3.200	1.650	2.000	1.000	/	650	1.500	235	1.500	2.000	5.900